

Technical Data

Type	Setting range (A)	Norminal current (A)			Aux. Contact (option)	Applied contactors
		Min	Med	Max		
GTH-22	0.14	0.1	0.14	0.16	1NO 1NC Auto/ manual	GMC-9 12 18 22
	0.21	0.16	0.21	0.25		
	0.33	0.25	0.33	0.4		
	0.52	0.4	0.52	0.63		
	0.82	0.63	0.82	1		
	1.3	1	1.3	1.6		
	2.1	1.6	2.1	2.5		
	3.3	2.5	3.3	4		
	5	4	5	6		
	6.5	5	6.5	8		
	7.5	6	7.5	9		
	8.5	7	8.5	10		
	11	9	11	13		
	15	12	15	18		
	19	16	19	22		
GTH-40	5	4	5	6	1NO 1NC Auto/ manual	GMC-32 40
	6.5	5	6.5	8		
	7.5	6	7.5	9		
	8.5	7	8.5	10		
	11	9	11	13		
	15	12	15	18		
	19	16	19	22		
	22	18	22	26		
	30	24	30	36		
	34	28	34	40		
GTH-85	8.5	7	8.5	10	1NO 1NC Auto/ manual	GMC-50 65 75 85
	11	9	11	13		
	15	12	15	18		
	19	16	19	22		
	22	18	22	26		
	30	24	30	36		
	34	28	24	40		
	42	34	42	50		
	55	45	55	65		
	65	54	65	75		
	74	63	74	85		